REMOTE SENSING/GIS INTEGRATION FOR SITE PLANNING AND RESOURCE MANAGEMENT

J. D. Fellows
University of Maryland, Department of Civil Engineering
College Park, Maryland 20742

ABSTRACT

In the late 1970's, the Maryland National Capital Park and Planning Commission, the county level planning offices for Montgomery County, Maryland, was faced with the problems of managing the rapid growth of their 400 square mile jurisdiction. The planning board decided digital data bases would be constructed capable of site planning and defining parameters necessary for energy, planning, hydrologic, economic and various resource forcasting models. Techniques for managing and collecting regional ancillary data (aerial photos, soils, etc.) and digital remote sensed data sets would be required to run models and produce timely graphics/statistics for present/proposed decision-making. Concurrently, the University of Maryland Civil Engineering Department (UOMCE) was developing a computer-based gridded information system (GIS) allowing engineers to create, access, integrate, and maintain a multi-parameter geographical data base for real-time hydrologic modeling.

By joining forces, the UOMCE and MNCPPC developed an interactive/batch GIS (array of cells georeferenced to USGS quad sheets) and interfacing application programs (e.g., hydrologic models). This system allows non-programmer users to request any data set(s) stored in the MNCPPC data base by inputing any random polygon's (watershed, political zone) boundary points. The data base information contained within this polygon can be used to produce maps, statistics, and define model parameters for the area. Present/proposed conditions for the area may be compared by inputing future usage (land cover, soils, slope, etc.).

This system, known as the Hydrologic Analysis Program (HAP), is currently operational on the MNCPPC's HP 3000 mini-computer and the UOMCE UNIVAC-1180 main-frame computer. HAP has been especially effective in the real-time analysis of proposed land cover changes on runoff hydrographs and graphics/statistics resource inventories of random study area/watersheds.

INTRODUCTION

In August of 1977, the Montgomery County Offices of The Maryland National Capital Park and Planning Commission incorporated an adaptation of a computer-based geographical information system known as MSDAMP. MSDAMP, an acronym for Multi-Spatial Data Analysis Mapping Program, was developed at the Iowa State University Land Analysis Laboratory in November 1972. This effort allowed cultural and physical data from existing maps and aerial photographs to be converted to a digital format and stored on the County's computer. The dominant land use or other desired parameter for each of these cells is encoded and entered into the computer. In batch mode, MSDAMP can be used to produce line printer gray-scale maps showing the distribution of various land uses, geologic features, slopes, soils, etc.

The data structure of MSDAMP is an array of five-second cells covering the entire 400 square mile Montgomery County. Each cell, encompassing an area of 4.58 acres, measures 397.75 feet east/west and 505.90 feet north/south. These dimensions were selected to give the five second increment at a latitude of 39°00'00" and allow distortion-free symbolic maps to be produced with ten column by eight line high speed line printers. At this cell resolution, each data plane (land cover, soils, etc.) in the Montgomery County data base would contain 55895 cells. MSDAMP requires the input of each individual cell georeferenced by latitude and longitude. In the subsequent years MSDAMP proved to be generally ineffective because of this cumbersome data collection method, inability to interface with application programs (e.g., hydrologic and planning models) and inefficient sequencial data base searches.

In 1978, the University of Maryland Civil Engineering Department (UOMCE) was conducting research in geographical information systems (GIS) for hydrologic analysis. The goal of the UOMCE GIS was to improve large area geoencoding techniques, provide a data structure capable of manipulating random polygons of data within the data base, interface the data base with existing hydrologic models, and manage the data base consisting of both digital remote sensed data (Landsat, digital terrain) and ancillary hard copy information (aerial photography and soil maps).

By joining forces, the MNCPPC and UOMCE created a system called the Hydrologic Analysis Program (HAP) which satisfied both organizations goals. The MNCPPC involvement ensured that the HAP software/hardware requirements would be developed for a non-programmer county level production environment.

It was decided that the HAP data collection, data management, and model interface would be tested by expanding the MNCPPC data base to include land cover, hydrologic soil groups and slope necessary for defining parameters in the Soil Conservation Service hydrologic model, TR-55. In a typical real-time situation, the planner types the coordinates of a water-shed boundary on the keyboard of an office terminal connected with a Hewlett-Packard 3000 mini-computer. The appropriate HAP compatible MSDAMP

data files are automatically accessed and the planner's terminal immediately produces:

- a series of symbolic maps showing the distribution of land use, soil type, and slope;
- statistical tables showing the number of acres and the percentage of the watershed area devoted to each land use, soil type, or slope category;
- 3. a table showing the runoff curve number, hydraulic length, and time of concentration needed to enter the SCS model.

If the planner also enters a rainfall amount into the terminal, HAP will automatically list the volume of runoff and estimated peak discharge as computed with SCS-TR-55.

A major function of HAP is to give planners the capability to assess the impact of land use or other changes being considered for the watershed. Thus, after the above information has been obtained for existing conditions, the planner can type the coordinates of those subareas being considered for change into the keyboard. He lists the type of new land use or other changes being considered for each of these subareas. The program then recycles in the manner outlined above with the new subarea information to give data for the watershed under new conditions.

HAP MODEL

The guiding principle in the development of HAP was that planners must be able to obtain quantitative information in real time for any watershed/political zone in the County. This pilot HAP model consists of three major components: 1) an enhanced GIS designed for collecting and manipulating the data base; 2) the interface between the data base and SCS-TR-55 hydrologic model; and 3) graphics/statistic package.

HAP Gridded Information System

The HAP GIS was designed to simplify the user's maneuvering of data between the hierarchical levels of the data base. This task was accomplished by providing the user with a hierarchical STUDY AREA-7½° UNITED STATES GEOLOGICAL SURVEY (USGS) TOPO SHEET-GRID-CELL-ATRIBUTE model. Figure 1 shows the Montgomery County, Maryland study area subdivided into its nineteen USGS topo sheets. Each topo consists of 90x90 grid of 4.58 acre cells containing various geophysical attributes. The cells are georeferenced by latitude/longitude and grid row/col.

The concept of storing geographical information in a computer can be illustrated by Figure 2. Conceptually, the spatial distribution of the geographical quantities are coded as an array of rectangular cells with the position of each cell identified by a row and column number. The dominant




Figure 1

Quad-Sheet Storage Arrangement For Montgomery County, Maryland




Figure 2
Concept of Single Variable
Data Bank
(from the Corps of Engineers¹)

Figure 3
Storage of Multivariable Information In A Grid Cell Data Base

(from the Corps of Engineers 1)

STORED DATA FILE

geographical quantity within each cell is identified, generally, by a single valued alphanumeric character. This information is stored in the computer in some format similar to that listed in the lower part of Figure 2. The strategy illustrated by Figure 2 can be extended to a system in which layers of geographic information are reduced to the same format, added to the computer and interfaced with each other to produce multivariant parameters, such as those required for hydrologic models. Figure 3 is a schematic illustrating the organization of a multi-parameter data base.

Using the HAP model as a loading template, HAP will accept data by the gird-overlay featured in Figure 2, digitized polygons or previously existing gridded digital data. The electronic digitization of single-valued polygons is very efficient for homogeneous data attributes like hydrologic soil groups. The polygons are converted to grid cells within HAP. To minimize collection efforts, an entire topos grid is tagged with the dominant data class. Only the cells containing subsequent data classes are actually geoencoded.

The model also allows an engineer or planner to use the quad sheet as a "pointer" and, thereby, manipulate only the data within the quad sheets involved in an analysis, rather than the entire MSDAMP data base. For example, if a planner was interested in the analysis of the shaded watershed shown in Figure 1, the first step would be to type in the topo access numbers 2542, 2819, 3650, and 3927. This would cause the computer to access the tape or other off line inexpensive storage and bring the 90 x 90, 5-second arrays of cells contained within the Gaithersburg, Sandy Spring, Rockville, and Kensington quadrangle sheets into temporary direct access storage. The role of the topo access will be explained in a subsequent section.

Table I lists the land use categories accessed by HAP from the MSDAMP data base. Unless specified by the planner from the terminal, the symbols listed in Table I will be used by HAP in printing any maps requested in the output. The planner has an array of options including the assignment of "blanks" to some of the categories, or all but one, in order to produce special purpose thematic maps. The Curve Numbers listed in Table I will be discussed in the following section.

Table II lists the slope categories and their map symbols stored in the HAP data base. Ranges of slopes, rather than specific slope values, are used in order to allow the slope within a cell to be represented as a single digit and, thereby, minimize the storage requirements.

HAP Hydrologic Model

The power of the system is realized when these arrays of stored variables are interfaced directly through the computer with simulation models. In this approach, cells within a watershed are combined to define the input parameters needed for the hydrologic model. The model then outputs desired streamflow characteristics in a format appropriate to the user's requirements.

Table I

Land Cover Symbols and Curve Numbers
Used In Hydrologic Analysis Program

LAND COVER CATEGORY	SYMBOL	CURVE	NUMBER F	OR SOIL	CROUP
			В	(Į
Grass		39.	61.	74.	80.
Cultivated Fields	С	72.	B1.	85.	91.
Conifer Forests	Σ	25.	55.	70.	77
Deciduous Forests	,	25.	5 5.	70.	77
ldle lands	c	49.	69.	79	84
Rural Residential	,	51.	68.	79.	84
Industrial/commercial	, z	89.	92.	94.	95
Single Family	1	61.	75.	83.	87
Low Density	н	57.	72.	81.	86
High Density	n	77.	85.	90	92

Table II

Slope Category Symbols Used In Hydrologic Analysis Program

SLOPE RANCE	SYMBOL
0.0 LE PERCENT SLOPE LT .25	A
.25 LE PERCENT SLOPE LT .50	3
.50 LE PERCENT SLOPE LT .75	c
.75 LE PERCENT SLOPE LT 1.0	D
1.0 LE PERCENT SLOPE LT 1.5	E
1.5 LE PERCENT SLOPE LT 2.0	F
2.0 LE PERCENT SLOPE LT 2.5	6
2.5 LE PERCENT SLOPE LT 3.0	В
3.0 LE PERCENT SLOPE LT 4.0	1
4.0 LE PERCENT SLOPE LT 6.0	3
6.0 LE PERCENT SLOPE LT 8.0	k (
8.0 LE PERCENT SLOPE LT 10.0	l L
10.0 LE PERCENT SLOPE LT 12.5	и
12.5 LE PERCENT SLOPE LT 15.0	l pe
15.0 LE PERCENT SLOPE LT 20.	0
20.0 LE PERCENT SLOPE LT 25.0	7
25.0 LE PERCENT SLOPE LT 30.0	Q
30.0 LE PERCENT SLOPE LT 40.0	R
40.0 LE PERCENT SLOPE LT 50.0	5
50.0 LE PERCENT SLOPE LT 75.0	7
75.0 LE PERCENT SLOPE LT 100.	ט
100. LE PERCENT SLOPE LT 200.	V
200. LE PERCENT SLOPE LT 300.	u
300. LE PERCENT SLOPE LT 300.	x
SOO. LE PERCENT SLOPE	¥

LE - LESS OR EQUAL TO

*LT - Less than

The model used to generate the volumes of runoff and peak discharges from the information available in the data base is a computerized version of parts of SCS-TR-55². It is assumed that the HAP user has or will develop an understanding of SCS-TR-55. Thus, only the key equations needed to explain the logic flow of HAP will be presented.

The implementation of HAP starts with the user drawing a boundary around the watershed of interest on USGS $7\frac{1}{2}$ minute quad sheets. Names of the quad sheets involved and a sufficient number of points to adequately define the boundary are entered into the terminal. The internal software of HAP then isolates the cells contained within the watershed boundary. The land use and hydrologic soil group are interfaced to compute a curve number for each cell in accordance with Table I. The cells are then summed and divided by the total to obtain an average Curve Number for the watershed. In a similar fashion, the average slope is obtained for the watershed. Table III lists the symbols that will be used to print HAP soil maps if desired.

After the Curve Number, CN, has been derived, the relationship

$$S = (\frac{1000}{CN}) - 10 \tag{1}$$

is then used to compute the potential maximum storage, S, of the watershed. The result of this computation is then entered into

$$Q = \frac{(P - .2S)^2}{P + .8S}$$
 (2)

to obtain the volume of runoff, Q, from the rainfall, P.

HAP obtains the area of the watershed, A, by counting the number of cells encompassed within the boundary and multiplying by 4.58. The area is then available to estimate the hydraulic length in accordance with

$$H_{L} = 209(A)^{6}$$
 (3)

The time of concentration is then estimated from

$$T_{c} = \frac{1}{0.6} \left(\frac{H_{L}^{\cdot 8} (S+1)^{\cdot 7}}{1900 \text{ y}^{\cdot 5}} \right) \tag{4}$$

where Y is the average slope of the watershed. Finally, the time of concentration is entered into a mathematical relationship defining the curve of Figure 4, to produce a dimensionless peak discharge which HAP converts to the peak discharge in cubic feet per second by multiplying the area in sq. miles by the volume of runoff obtained from Equation 2.

Table III
SOIL TYPE SYMBOLS USED IN HYDROLOGIC ANALYSIS PROGRAM

Symbol
A
В
С
ם




Figure 4 Peak Discharge in scm Per Inch of Runoff Versus Time of Concentration (T_C) for 24-hour, Type-II Storm Distribution.

The use of Figure 4 imposes the requirement that the rainfall used with HAP be a 24 hour volume so it will be consistant with the intensity distribution of the SCS Type-II Storm Rainfall. The SCS Type-II Storm is excellent for use in urban and urban fringe studies. The storm structure provides a period of several hours of light rainfall during which the soils are "wetted-up" to reduce infiltration rates and fill a portion of the depression storage. There is then a period of several hours of heavy rainfall simulating thunderstorm intensities. Finally, there is a period of lightening rainfall during the last several hours.

It should be recognized that there are a number of options within SCS-TR-55. One approach within TR-55 is to use detailed maps to measure incremental hydraulic flow lengths and then develop the time of concentration through velocity computations. HAP defines the hydraulic length and the time of concentration with the empirical Equations 3 and 4 which were developed by SCS from regression analyses of watersheds throughout the United States. A constraint on Equation 4 is that it be limited to watersheds of less than 2000 acres. Table IV contains Montgomery County rainfall-frequency values required by TR-55.

Table IV

24 Hour Rainfall in Inches for Different Frequency Events

for Montgomery County

Frequency	Rainfall Inches
1	2.6
2	3.2
5	4.2
10	5.1
25	5.6
50	6.3
100	7.2

USE OF THE HYDROLOGIC ANALYSIS PROGRAM FOR WATERSHED INVESTIGATIONS

The use of HAP as a tool for watershed investigations will be illustrated through the use of an example problem. The specific problem addressed is the comparison of the peak discharge for a watershed under present conditions with the peak discharge anticipated under conditions of complete development as allowed by the Montgomery County approved land use master plan. The statement of the example problem is as follows:

There is a need to provide stormwater storage behind and existing conduit on the Rockville quad. The design of the control structure that will create the backwater requires estimates of the peak discharge for present and future land use conditions for a 100 year, 7.2 inch, 24 hour storm. Determine the current and future peak discharges, volumes of runoff and percent changes created in these quantities by developing the watershed to its ultimate land use distribution.

HAP uses four "modules" during its execution. The function of these modules are:

BOUNDARY MODULE= The BOUNDARY module is called when the user wishes to enter the coordinates of the watershed boundary. The BOUNDARY module retrieves and stores the cells contained within the boundary of the study area.

HYDROLOGIC MODEL= The HYDROLOGIC MODEL module merges the cells within the boundary and computes the slope for the study area. These parameters are then interfaced with the SCS-TR-55 and volumes of runoff and peak discharges estimated for user input rainfalls. The user is also prompted for map production and statistical summaries of the study area for present conditions (i.e., land cover, soils, and slope).

UPDATE MODULE= The UPDATE module allows the input of proposed cell changes within the study area. The cell distribution in the watershed is adjusted for the proposed conditions interfaced with TR-55 and revised runoffs compared to the present conditions. The user is prompted for production of maps and statistical summaries describing the study area under proposed conditions.

STOP MODULE= The STOP module is called when the user has completed his study and wishes to exit from the HAP program.

The solution of the example problem will assume the user is accessing the program capabilities with a 132 character terminal. The program is interactive with the terminal outputing prompts and explanations to aid the user in inputing data or requesting HAP operations. Those terminal statements within boxes are input statements entered by the user. Those statements in upper case letters are outputs from the terminal.

The following run stream describing the steps in the solution of the example problem contains explanations of key points.

TYPICAL HYDROLOGIC ANALYSIS PROGRAM RUN STREAM

STEP ONE

GATHER NEEDED INFORMATION PRIOR TO ACCESSING HAP

Before working with the terminal, it is necessary, in the interest of efficiency, to tabulate the information necessary to define the watershed boundary and move the appropriate portion of the data base into direct access storage. The first step is to assemble the topographic sheets needed to define the watershed boundary. The watershed boundary is sketched. The 90 x 90 transparent mylar grid is overlaid on the quadsheet. Enough nodes are picked to allow the watershed boundary to be approximated as a series of straight line segments. In this example, the entire watershed is within the bounds of the Rockville quadrangle sheet. In order to get the data of this quadrangle into direct access storage, the user will have to enter the disk access number obtained from Figure 1, in this case 2819. user will also have to enter the latitude and longitude of the upper left hand corner of the quadrangle sheet. Finally, the cells to be changed to a proposed land cover will have to be tabulated for entry from the terminal. Thus, prior to accessing the terminal, the user would write down the information below.

> Latitude = 390730 Longitude = 771500 Disk Access No. = 2819

Tabulation of cell coordination of watershed boundary. Proceed clockwise. The boundary will automatically be closed between the first and last points listed.

Watershed Boundary

Boundary Point	Row	Column
1	04	50
2	04	53
	06	55
3 4	08	55 55
5	09	56
6	11	56
7	12	55
8	14	55
9	15	56
10	17	56
11	18	55
12	i 19	54
13	18	52
14	17	51
15	15	51
16	15	49
17	14	48
•		48
18	12	47
19	11	
20	07	47

Tabulation of cells to be changed to reflect proposed watershed conditions. The cell location and proposed land cover change within each cell is tabulated using the transparent mylar grid and the land cover codes of Table I . If soil type or slope were to also be changed, Tables II and III would be used to obtain the proper symbols.

LOCA	TION	NUMBER OF CELLS	LAND	SOILS	SLOPE
ROM	COLUMNS		COVER		
4	50-52	3	l k	zero	zero
5	49~54	6	k	''	"
6	50-55	6	k	11	"
7	49-55	7	k	"	11
8	49-55	7	k	''	"
9	49-56	8	k	-,,	11
10	48-56	9	k	"	"
11	47-56	10	k		11
12	48-53	6	k	 -	
13	50-53	4	k	"	"
14	50-53	4	k		"
15	51-52	2	k	- "	1,

If more than one quadrangle is involved, this process will be repeated for each sheet.

STEP TWO

SIGN ON HEWLETT PACKARD 3000 AS FOLLOWS

- (a) Turn on Terminal
- (b) Wait for green light
- (c) Hit return key
- (d) You will get a colon back
- (e) Type in (HELLO USER.MPLENV, WATER)
- (f) It will ask you for Password
- (g) Type in ENVIRON
- Type in NAZ (h)
- (i) You will get # sign
- To execute HAP you type in HAP (j)

THE TERMINAL INPUTS AND OUTPUTS FOR STEP 2 ARE:

CONCERNED CONTROL OF THE PROPERTY OF THE PROPE **ENTER: BOUNDARY, HYDROLOGIC MODEL, UPDATE, LOAD, STOP**

Note: At this point the terminal will stop. The output immediately above lists the modules available. HAP is ready to accept the input of the watershed boundary.

STEP THREE BOUNDARY MODULE

- Α. Request the BOUNDARY module by typing BOUNDARY into the terminal.
- B. Specify if you need input prompts.
- C. Enter name of study area.
- Enter number of topos containing study area. D.
- E. Enter latitude and longitude of northwest topo corner.
- Enter DAF topo address (see Figure 1) F.
- G. enter whether boundary points are P=POLYGON or C=CELL format.
- H. Enter whether boundary points are I=INTEGER or D=DIGITAL.
- In this example the boundary is defined from the northeast corner row and column coordinates of a 90 x 90 (4.58 acre) cell grid. If the boundary points were entered from a digitizier the map scale would be requested. The program is set up to accept the node points from a digitizer in inches (eight sets of X, Y coordinates per card in F5.2 format).

THE TERMINAL INPUTS AND OUTPUTS FOR STEP 3 ARE:

ROMONY HORLE
000 YOU NEED DATA INPUT PROMPTS (Y/N) 00
SHAME OF STUDY AREA (NAX 30 CHAR) ++
ROCKULLE MATERSHED ANALYSIS
OFFICER: TOPO LATITUDE LONGITUDE DISK ADDRESS.
(*P*=PQ_YSON_OR "C" CELLS DATA SET),("I"=INTERER CR "B"=BISITAL DATA) [380730.771500.2819.F.I]
ENTER; ROM, COL (TERMINATE NITH ENDO)
18.8
9.56
11.55 12.55
14.33 15.55
177.36 18-55
18.54 18.52
17.51 15.51
15.49 14.48
12.46
7.47 EBB0
TOPO-2819 LAT-390730 LON-771500 BDYPTS: 20


STEP FOUR

HYDROLOGIC ANALYSIS

The Hydrologic Analysis Program heading listing the modules is on the terminal output. The cells within the watershed boundary have been assembled. HAP is ready to do the TR-55 analysis.

- A. Request the HYDROLOGIC MODEL module.
- B. Input rainfall (inches).
- C. Specify if present condition land cover, soils, and slope maps are to be generated and to what unit they should be transmitted.

THE TERMINAL INPUTS AND OUTPUTS FOR STEP 4 ARE:



```
-- DO YOU WANT A MAP OF MONTGOMERY COUNTY MYSRO SOIL (Y/M)++
   YOU WANT DEFAULT OR NEW MAP SYMBOLS (D/M)?++
      4 ! 8888
5 ! 88888C88
6 ! 88888C88
7 !888D68D68
 0715
                                       390715
                                       390710
390705
390700
390710
390705
390700
                                       390655
     1888088888
300655
390650
390645
                                      1Ō
390540
                                       390635
390630
390625
390620
390615
390605
390605
390555
390530
390545
                                      12
                                      13
                                      15
    390550 21 | •
390545 22 | •
390540 23 ! SYN CLASS
                                  1 + 1 23
                                       390540
390535
                                      24
390530 25 | e
390525 26 | e
390520 27 | e
390515 28 | e
                            408.03 76.72 • 25 390530
22.92 4.31 • 26 390525
100.86 18.97 • 27 390520
531.81 100.00 • 28 390515
         TOTAL
     390510 29
      -
```

2000 YOU MANT A MAP OF MONTGOMERY COUNTY 2 SLOPE (Y/N)++ YOU HANT BEFAULT OR NEW MAP SYMBOLS (B/N)?++ 789012345678901234567890123456789012345678901234567890123 380715 380710 380705 380700 JJII KJKKJH IKKJJAGJ IFGJJIJHFI 4 ! 390715 5 ! 6 ! 7 !! 390710 390705 390700 8 390535 8 390530 10 390645 11 390640 12 390635 13 390630 14 390625 390655 8 (61KKJJJJ 390650 8 (FEEJJIIHJ 390645 10 (HIJJJFIII 390645 10 MIJJFIIII 390640 11 BJJEHGIIH 390635 12 JJEGFDFI 390630 13 I IKKIFGFF 390625 14 MIJHGFNH 390620 15 MIJHGFNH 390615 16 FIIIFD 390610 17 I IIIJJJ 390605 18 FJHI 390600 19 JJ 15 390620 16 390615 17 390610 18 390605 19 390600 789012345678901234567890123456789012345678901234567890123 תתוחות החוות ה החוות החBIO NAP NODULE.....

ENTER: BOUNDARY.NYDROLOGIC MODEL.UPDATE.LOAD.STOP

STEP FIVE

ENTER PROPOSED CHANGES OF STUDY AREA AND COMPARE SCS TR-55 RESPONSE FOR PRESENT/PROPOSED CONDITIONS

The heading listing the modules has output on the terminal. The SCS-TR-55 analysis for current conditions is complete. HAP is ready to accept changes within the watershed and repeat the SCS-TR-55 analysis. If there are no watershed changes to be investigated, proceed to Step Six to exit program.

- A. Request the UPDATE module.
- B. As prompted, select the quads requiring changes.
- C. Enter the location and proposed land cover, soil, or slope value for each update cell from Tables I, II, and III. In this case, only land covers are being changed.
- D. For the given rainfall in STEP FOUR, the updated conditions will be routed through TR-55 and the response compared with the present conditions.
- E. The user will be prompted for proposed condition maps to verify the update input.

THE TERMINAL INPUTS AND OUTPUTS FOR STEP 5 ARE:

REFERENCES SERVICES DE SERVICES DE SERVICES DE LA CONTRACTOR DE LA CONTRACTOR DE CONTR
SHARE THERE MAY CHANGES IN THE 390730 771500 TOPO(Y/M)++
NT
OF THE CHANGE INPUT A ZERO (TERMINATE MITH ENDO) OF
4.30.3.8.8.8 1
6.50.6.K.0.0
8.49.8.X.0.0
10,48,8,K,0,0
11,47,10,8,0,0 12,48,6,8,0,0
13.50.4.K.0.0
14.50.4.K.0.0 [15.51.2.K.0.0 [
E1090
endMTERSHED MMLYSIS (BCS-TR-55) ens
IDENTIFICATION-ROCKVILLE MATERSHED AMALYSIS
MAINFALL(INCHES): 7.20
BAINFALL(INCHES)= 7.20 BRAINAGE AREA(ACRES)= 331.81 .83 (SRUARE HILES) MYDRAULIC LENGTH(FEET)= 8028.18 BLANTITY PRESENT PROPOSED
BAINFALL (INCHES): 7.20 BRAINAGE AREA (ACRES): 331.81 .83 (SRUARE MILES) MYDRAULIC LENGTH (FEET): 8028.18 BLANTITY PRESENT PROPOSED CLRVE NURBER 71.75 86.23
BAINFALL(INCHES)= 7.20 DRAINFALL(INCHES)= 931.81 .83 (SRUARE HILES) HYDRALLIC LENGTH(FEET)= 8028.18 BLANTITY PRESENT PROPOSED CURVE NUMBER 71.75 86.23 AVERAGE PERCENT BLOPE 3.67 3.67 THE OF COMEENTRATION(HOURS) 2.05 1.30
BAINFALL(INCHES)= 7.20 BRAINFALL(INCHES)= 531.81 .03 (SRUARE HILES) MYDRAMALIC LENGTH(FEET)= 9028.18 BLANTINE PROPOSED CURVE NUMBER 71.75 85.23 SWERACE PERCENT BLOPE 3.67 3.67
BAINFALL(INCHES)= 7.20 BRAINFALL(INCHES)= 931.81 .83 (SRUARE HILES) HYDRAULIC LENGTH(FEET)= 8028.18 BLANTITY PRESENT PROPOSED CLEVE NUMBER 71.75 85.23 AVERACE PERCENT BLOPE 3.67 3.67 TIME OF CONCENTRATION(HOURS) 2.05 1.30 VOLUME OF RUNOFF 3.87 5.58
BAINFALL(INCHES)= 7.20 BRAINFALL(INCHES)= 731.81 BRAINFALL(INCHES)= 331.81 BRAINFALL(LENGTH(FEET)= 8028.18 BLANTIN PROPOSED CLRVE NUMBER 71.75 86.23 BURNACE PERCENT BLOPE 3.67 3.67 TIME OF CONCENTRATION(HOURS) 2.05 1.30 VOLUME OF RANOFF 3.87 5.58 PEAK DISCHARGE (CF8) 838.83 1244.89
BAINFALL(INCHES)= 7.20 BRAINFALL(INCHES)= 731.81 .83 (SRUMRE HILES) HYDRAULIC LENGTH(FEET)= 8028.18 BLANTITY PRESENT PROPOSED CURVE NUMBER 71.75 86.23 MARRACE PERCENT BLOPE 3.67 3.67 THE OF CONCENTRATION(HOURS) 2.05 1.30 VOLUME OF RUMOFF 3.87 9.58 PEAK DISCHARGE (CFB) 838.83 1244.89 ***CHANGE IN BUNGFF 1.81 (INCHES) 40.57 %**** ***CHANGE IN PEAK DISCHARSE 805.06 (CFS) 84.60 %****
BAINFALL(INCHES)= 7.20 BRAINFALL(INCHES)= 731.81 BRAINFALL(INCHES)= 331.81 BRAINFALL(LENGTH(FEET)= 8028.18 BLANTIN PROPOSED CLRVE NUMBER 71.75 86.23 BURNACE PERCENT BLOPE 3.67 3.67 TIME OF CONCENTRATION(HOURS) 2.05 1.30 VOLUME OF RANOFF 3.87 5.58 PEAK DISCHARGE (CF8) 838.83 1244.89
BAINFALL (THEMES) = 7.20 BRAINFALL (THEMES) = 7.20 BRAINFALL (THEMES) = 7.20 BRAINFALL ACRES) = 7.20 BRAINFALL ACRES) = 7.20 BRAINFALL ACRES = 7.20 BRAINFALL ACRES = 7.20 BRAINFALL ACRES = 8028.18 BLANTITY PRESENT PROPOSED CLEVE NUMBER 71.75 86.23 AMERICE PERCENT BLOPE 3.67 3.67 THE OF CONCENTRATION (NOURS) 2.05 1.30 VOLUME OF RUNCH 3.87 5.58 PEAK DISCHARGE (CFB) 829.83 1244.69 ***CHANGE TH RUNCH
BAINFALL(INCHES)= 7.20 BRAINFALL(INCHES)= 731.81 .G3 (SRUARE HILES) MYDRAALIC LENGTH(FEET)= 8028.18 BLANTITY PRESENT PROPOSED CLEVE NUMBER 71.75 86.23 AVERAGE PERCENT BLOPE 3.67 3.67 TIME OF CONCENTRATION(HOURS) 2.05 1.30 VOLUME OF RANGET 3.87 5.38 PEAK DISCHARGE (CFB) G39.83 1244.89 ***CHANGE IN PUNDFF 1.81 (INCHES) 40.57 I*** ***CHANGE IN PEAK DISCHARGE 805.06 (CFB) 94.60 I*** IN ACCORDANCE MITH THE BCS METHOD OF ESTIMATING VOLUME OF

1111111111111111110000000000000000000	100 YOU 1	MANT A MAP OF HONT. CO A	SYMBOLS (B/N)?++		
### ### ##############################		77777777777777777777777777777777777777	77777777777777777777777777777777777777	777777777777 000000000000000000 77777777	
### BO655	190715- 4-	44455555555555666666666666666666666666	567777777777888888888888888888888888888	000000000001111 89999999990000 901234567890123	44 29 07
80540 Z3	80655 8 80650 9 80645 10 80640 11 90635 12 90630 13 80625 14 90625 15 90610 17 90605 18 80655 20 80555 20	RAKRAKER RAKKKKKK KAKKKKKK KAKKKKKK KAKKKKKK KAKKKKKK			1- 7 280 70 1- 8 3906 1- 8 3906 1- 10 3906 1- 12 3906 1- 12 3906 1- 13 3906 1- 15 3906 1- 16 3906 1- 17 3906 1- 18 3906 1- 19 3906 1- 20 3905 1- 20 3905 1- 21 3905
90510 29	90540 23 90535 24 90530 25 90525 26	ROCKVILLI HONT, CO	MATERSHED AMALYSIS AER. PHOTO LAND COVE	R .	! 23 39054 ! 24 39053 ! 25 39053 ! 26 39053
00000000000000000000000000000000000000	80515 28 90510 29 90505 30 80500 31 90453 32 90450 33	B GRASS F BECIDUOUS FORES I INDUSTRIAL/COM L SINGLE FAMILY TOTAL	ETS ERCIAL 3	50.43	28 3905 29 3905 30 3905 31 3905 22 3904 33 3904 34 3904
77777777777777777777777777777777777777	30435 36	44455555555556668666	00000000000000000000000000000000000000	00000000001111 8999999999999000	! 36 39043
100554433221100554433221100554433221100554433221100554433 0505050505050505050505050505050505050		77777777777777777777777777777777777777	77777777777777777777777777777777777777	77777777777777777777777777777777777777	

STEP SIX EXIT HAP

The heading listing the modules has output on the terminal. The analyses are complete and you are ready to exit from the program by calling the 'STOP' module.

THE TERMINAL INPUTS AND OUTPUTS FOR STEP 6 ARE:

STOP NORMAL HAP EXIT

These interactive inputs may be placed in a data file prior to HAP execution. HAP can be instructed to receive inputs from this file creating a quasi-interactive terminal session. This mode is especially advantageous when testing the same watershed for many different rainfall rates.

CONCLUSION

Because of its interactive, real-time capabilities, the Hydrologic Analysis Program (HAP) is very valuable as a tool to assist in decision making processes. Although it is optimized for water resource analyses, HAP's ability to access any area or cell within the MSDAMP data base and then produce statistical tabulations or symbolic maps should make it an extremely attractive tool for an array of problems encountered by county officials. HAP is currently operational on the MNCPPC's HP3000 minicomputer and the UOMCE UNIVAC 1180 main frame computer.

REFERENCES

- U.S. Army Corps of Engineers, 'Guide for the Creation of Grid Cell Data Banks', Hydrologic Engineering Center, USACE, Davis, Calif. Sept. 1978.
- 2. U.S. Department of Agriculture, Soil Conservation Service, SCS-TR-55
- 3. U.S. Department of Commerce, Technical paper 40